WOW
WATER·ON·WATER™
REVERSE OSMOSIS

WOWRO 50 / 20-210-001

- Faster Easier Installation
- Compact size fits in half the space of other units
- Patented **water-on-water**™ tank provides constant flow to the last drop
- Environment-friendly – uses up to 500% less waste water
- No air charge needed
- Patented manifold design increases reliability
- Patented CPU valve with only one moving part = higher reliability
- Operates as low as 20 psi
- New Leak Detection/Shut-off System

Specifications	
Model:	WOWRO 50 / 20-210-001
Temperature Range:	40° F (4.44° C) - 100° F (37.77° C)
Pressure Range:	20 - 125 psi (1.38 - 8.62 Bar)
Membrane Rating:	50 gpd (186.27 Lpd)
Efficiency Rating:	27.50%
TDS Rejection:	95.40%
Dimensions:	14" x 9-1/2" x 10-1/2"
Weight:	11.5 Lbs

The installation of this RO System needs to comply with all Local and State Laws and Regulations

C IAPMO ®

IAPMO R&T WATER QUALITY PLATINUM SEAL IAPMO RESEARCH AND TESTING

This WOW-50 RO System is Certified by IAPMO R&T against NSF/ANSI 58 for the reduction of Claims specified in the Performance Data Sheet

Efficiency rating means the percentage of the influent water to the system that is available to the user as reverse osmosis treated water under operating conditions that approximate typical daily usage

The Many Uses of WOW Water

- Cooking
- Juices & Mixes
- Coffee & Tea
- Ice Cubes
- Humidifiers
- Aquariums
- Rinsing Hair
- Plants
- Steam Irons
- Windshield
- Wiper Fluid
- Automobile Batteries

Do not use with water that is micro-biologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts.

Compact Size. Easier Install. More Reliable.

WOWwater.com

* Results may vary depending on water conditions
WOW Water Technologies– A Beall Development – 217 S. Pacific Coast Hwy, Redondo Beach, CA 90277
- U.S. and foreign patents issued and pending.

SHIPPING SPECIFICATIONS

PART NUMBER	MODEL	DESCRIPTION	CARTON QTY	CARTON DIMENSIONS	CARTON WEIGHT
20-210-001	WOWRO 50	4 Stage Reverse Osmosis System Hardware not included	1	16"L X 11"W X 13"H	11.5 LBS
20-201-001	WOWRO 50	Pre Filter Cartridge	20	16"L X 13"W X 11"H	13 LBS
20-202-001	WOWRO 50	Post Filter Cartridge	20	16"L X 13"W X 11"H	18 LBS
20-250-001	WOWRO 50	RO Membrane Cartridge	20	16"L X 13"W X 11"H	17 Lbs
PART NUMBER	**MODEL**	**DESCRIPTION**	**PALLET QTY**	**PALLET DIMENSIONS**	**PALLET WEIGHT**
20-210-001	WOWRO 50	4 Stage Reverse Osmosis System Hardware not included	50	40"L X 48"W X 68"H	640 LBS
20-210-001	WOWRO 50	4 Stage Reverse Osmosis System Hardware not included	25	40"L X 48"W X 42"H	340 LBS

PERFORMANCE

MODEL WOWRO 50 / 20-210-001

This WOW50 RO system is certified by IAPMO R&T against NSF/ANSI 58 for the reduction of claims specified in this document.

Membrane Rating: 50 gpd (186.27 lpd)

Efficiency Rate: 27.5%

TDS Rejection: 95.4%

This WOW-50 RO System is Certified by IAPMO R&T against NSF/ANSI 58 for the reduction of Claims specified in the Performance Data Sheet

Efficiency rating means the percentage of the influent water to the system that is available to the user as reverse osmosis treated water under operating conditions that approximate typical daily usage

Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. Systems certified for cyst reduction may be used on disinfected water that may contain filterable cysts

WOW WATER SYSTEMS
WOW Water Technologies, Inc

217 S. Pacific Coast Hwy, Redondo Beach, CA 90277
310-375-5000 ~ 866-790-8911 wowwater.com